

Specification and scope of supply of P50.20

| Description | Specification/scope of supply |
|--|---|
| Max component length | 884mm |
| Max component width | 589mm |
| Max component thickness | 150mm |
| Max component weight | 100kg – UDL (Uniformly Distributed Load) |
| Measuring accuracy, length & width** | +/- 20/40 µm* |
| Measuring accuracy, height** (Optional) | +/- 100 µm |
| Measuring speed** | <0.25sec |
| Camera | Industrialised ultra high resolution professionally mounted in sealed enclosure |
| Dot Laser height measuring device (Optional) | Class III R precision laser |
| Computer processor | Intel Quad or Dual Core |
| Processor speed | <3GHz |
| Hard disk | <125Gb |
| Screen | 20 inch flatscreen or better |
| Peripheral equipment | Keyboard and optical mouse |
| Operating software | Windows 10- 64 Bit |
| Proprietary InspecVision software | Inspection, SPC, Reporting, Reverse engineering |
| Data cable | USB2 or USB3 |
| Computer cabinet (Optional) | Industrial dust-proof enclosure |
| Light table construction | Extruded aluminium frame with acrylic cladding |
| Light table measuring surface | Laminate glass, toughened with integral diffusion layer |
| Light source | High efficiency LEDs |
| Mast construction | Extruded aluminium |
| Power supply | 230 Volt, single phase, 50Hz or 110 Volt, single phase, 60Hz on request |
| Power consumption | 6 Amp maximum at 230 Volt, 10 Amp max at 110 Volt |
| Control panel | Control switches for power, camera and lights. Main power indicator |
| EC directives | Compliant with Machinery, Low voltage and EMC Directives |
| Colour | Natural aluminium and blue acrylic |
| Ambient operating conditions | 10-30 degree C |
| Approx Footprint/installed width/ depth/ height/ weight of installed Light table and Mast | 1120 (W) x 983mm (D) x 2376mm (H) <200kgs |
| Approx Footprint/installed width/ depth/ height/weight of installed Computer Cabinet (inc keyboard tray) <i>Optional</i> | 587mm (W) x 900mm (D) x 1675 (H) <100kgs |
| Standard packing | Export crates suitable for sea shipping |
| Warranty | One year limited warranty on hardware and software |
| Optional extended warranty | Two or three year extended warranty (requires software upgrade option) |
| Software support option | Annual support contract provides free software upgrades |

*The first accuracy value specifies the accuracy achieved over most of the table, the second accuracy value specifies the accuracy achieved at table edges

**Accuracy results are verified on standard production machines using tests based on ISO 10360

Actual measuring accuracies achieved will depend on operating environment, user input, quality and condition of materials

Errors and omissions excepted

Due to our policy of continuous improvement specifications are subject to change without notice, please contact factory or your InspecVision dealer







Manufacturer:
InspecVision Ltd
 10 Trench Road
 Mallusk
 Newtownabbey BT36 4TY
 Co Antrim United Kingdom

Telephone: +44 (0) 28 90 844 012
Telefax: +44 (0) 870 706 1614
Email: Info@InspecVision.com
Web Address: www.InspecVision.com

Distributor Details:

P50.20 Schematic



Dimensions in brackets are in inches