

# Specification and scope of supply of P360.35L

| Description   | Specification/scope of supply   |
|---|---|
| Max component length  | 3000mm  |
| Max component width   | 1220mm  |
| Max component thickness   | 350mm   |
| Max component weight  | 500kg   |
| Measuring accuracy, length & width**  | +/- 35 / 75 µm*   |
| Measuring accuracy, height** (optional)   | +/- 250 µm  |
| Point Spacing   | 0.33mm  |
| Measuring speed**   | <0.25sec  |
| Camera  | Industrialized ultra high resolution professionally mounted in sealed enclosure   |
| Computer processor  | Intel Quad Core   |
| Processor speed   | >3GHz   |
| Hard disk   | >125Gb  |
| Screen  | 20 inch flatscreen or better  |
| Peripheral equipment  | Keyboard and optical mouse  |
| Operating software  | Windows 10, 64 Bit  |
| Proprietary InspecVision software   | Inspection, SPC, Reporting, Reverse engineering   |
| Data cable  | USB2 or USB3  |
| KVM   | Keyboard, Video Display & Mouse stand (PC integrated into light table assembly)   |
| Light table construction  | Frame with removable sheet metal cladding   |
| Light table measuring surface   | Laminate glass, toughened with integral diffusion layer   |
| Light source  | High efficiency LEDs  |
| Mast construction   | Heavy folded sheet metal construction   |
| Power supply  | 230 Volt, single phase, 50Hz, (32A 230V IEC EE 60309 Plug to 32A 230V IEC EE 60309 Socket Lead supplied) or 110 Volt, single phase, 60Hz, (NEMA L5 30P to NEMA L5 30R lead supplied) on request |
| Power consumption   | 20 Amp maximum at 230 Volt, 30 Amp max at 110 Volt  |
| Protective devices  | Circuit breakers, mounted at rear of light table  |
| Control panel   | Control switches for power, camera and lights. Main power indicator   |
| EC directives   | Compliant with Machinery, Low voltage and EMC Directives  |
| Paint colour (powder paint)   | RAL5013 (cobalt blue)   |
| Ambient operating conditions  | 10-30 degree C  |
| Approx Footprint/installed width/ depth/ height/ weight of installed Light table and Mast | 3360mm (W) x 2199mm (D) x 4640mm (H) <1400kgs   |
| Approx Footprint/installed width/ depth/ height/weight of KVM)                            | 710mm (W) x 472mm (D) x 1739 (H) <95kgs   |
| Standard packing  | Export crates suitable for sea shipping (3 nos)   |
| Warranty  | One year limited warranty on hardware and software  |
| Optional extended warranty  | Two or three year extended warranty (requires software upgrade option)  |
| Software support option   | Annual support contract provides free software upgrades   |

\*The first accuracy value specifies the accuracy achieved over most of the table,  
the second accuracy value specifies the accuracy achieved in the lower accuracy region, typically at table edges  
\*\*Accuracy results are verified on standard production machines using tests based on ISO 10360

Actual measuring accuracies achieved will depend on operating environment, user input, quality and condition of materials  
Errors and omissions excepted  
Due to our policy of continuous improvement specifications are subject to change without notice, please contact factory or your InspecVision dealer  
Non-standard hardware, software or acceptance tests must be defined prior to purchase



**Manufacturer:**  
**InspecVision Ltd**  
 10 Trench Road  
 Mallusk  
 Newtownabbey BT36 4TY  
 Co Antrim United Kingdom

**Telephone:** +44 (0) 28 90 844 012  
**Telefax:** +44 (0) 870 706 1614  
**Email:** Info@InspecVision.com  
**Web Address:** www.InspecVision.com

Distributor Details:

# P360.35L Schematic

DIMENSIONS IN BRACKETS ARE IN INCHES

